

active loudspeakers

PUB-280 active 2 way loudspeaker

CONSTRUCTION	2-way Bass Reflex 8" woofer/compression tweeter 2 types: hard shell / soft shell
POWER OUTPUT	280 watts continuous RMS bi-amplified
LOW	200 watts continuous / 400 watts peak (8 ohm/0.10 % THD)
MID/HIGH	80 watts continuous / 120 watts peak (8 ohm / 0.10 % THD)
FREQUENCY RESPONSE	38 Hz - 22 kHz
MAXIMUM SPL	118 dB
CONNECTIONS	Combo XLR/Jack line-in + XLR line-out + 12 Vdc output
POWER SUPPLY	220 Vac 50 Hz / 115 Vac 60 Hz (manual switching)
SAFETY	Ground lift switch (anti-hum)
CONTROLS	Volume
MOUNTING/TRANSPORT	ø36 mm std. Mount / spring loaded carrying handle
DIMENSIONS	390 x 380 x 265 (mm)
WEIGHT	19.60 kg (ca. 44 lb)

The Schertler PUB-280 and PUB-380 Active Loudspeaker Systems are high-powered and designed to provide undistorted music reproduction at high levels. Versatile and compact, PUBs may be used as a PA system for small clubs, a monitor system for medium-sized stages, and as individual acoustic instrument amplifier systems.


PUB-280 is an active, bi-amplified system designed to deliver the mid and high ranges of a PA or monitor system, or act as a full-range instrument amplifier for most acoustic instruments. With 200 WRMS to the 8" woofer and 80 WRMS to the 1" compression tweeter, PUB-280 packs a lethal punch in a small package.

PUB-380 Active Bass Extension is designed to augment the PUB-280 in either PA applications or for use with bass or keyboards as a subwoofer. PUB-380 has 380 WRMS powering a 10" woofer in a bass reflex enclosure. Frequency range is 35 - 120 Hz.



PUB-380

PUB-280



PUB-280

S1-MONITOR


active loudspeakers

The Schertler PUB-280 and PUB-380 Active Loudspeaker Systems are high-powered and designed to provide undistorted music reproduction at high levels. Versatile and compact, PUBs may be used as a PA system for small clubs, a monitor system for medium-sized stages, and as individual acoustic instrument amplifier systems.

PUB-280 is an active, biamplified system designed to deliver the mid and high ranges of a PA or monitor system, or act as a full-range instrument amplifier for most acoustic instruments. With 200 WRMS to the 8" woofer and 80 WRMS to the 1" compression tweeter, PUB-280 packs a lethal punch in a small package.

PUB-380 Active Bass Extension is designed to augment the PUB-280 in either PA applications or for use with bass or keyboards as a subwoofer. PUB-380 has 380 WRMS powering a 10" woofer in a bass reflex enclosure. Frequency range is 35 - 120 Hz.

Photo Credit: Michael Strain (c) 2000
Artist: David Jacobs-Strain



PUB-380 active bass extension

CONSTRUCTION	Bass Reflex 10" woofer 2 types: hard shell / soft shell
POWER OUTPUT	380 watts continuous RMS 600 watts peak (8 ohm 0.10 % THD)
FREQUENCY RESPONSE	35 Hz - 120 Hz (-3db)
MAXIMUM SPL	120 dB
CONNECTIONS	XLR in-out; 2 XLR out with frequency cut at 120 Hz
POWER SUPPLY	220 Vac 50 Hz / 115 Vac 60 Hz (manual switching)
SAFETY	Ground lift switch (anti-hum)
CONTROLS	Volume
MOUNTING	2 x ø36 mm std. Mount (top and bottom)
DIMENSIONS	450 x 350 x 370 (mm)
WEIGHT	23.00 kg (ca. 50 lb)



PUB-380

PUB-280



PUB-280

PUB-380